

15° BNS Plastic Sheet Coil



NSDCN75

PPG1500™ Combo Trim Head

Part Number	Length	Diameter	Head	Color	# / Case	Cases/ Skid	
HSNS112113THC	1½"	.113	T-15	Cedar	1,600	80	
HSNS112113THT	1½"	.113	T-15	Tan/ Earth Tone	1,600	80	

For use when attaching decking (composite or wood) to Trex® Elevations™ and other metal joists (12-16 gauges). Color matching can be done on larger, special orders.



AERT 2008 Testing
 1½"x.113 Plastic Sheet Coil Shot Through ½" MoistureShield® Fence Picket into 1½"x16 ga. Allied Tube Galvanized Black Powder Coated Square Tubing averaged a maximum load of 556.25 lbs.



Mantis Clip® attaching Trex Transcends® composite decking to Trex Elevations™ Steel Frame with a Ballistic NailScrew®.

TIP For the best pull-out resistance, only allow three to five threads of the NailScrew® through the metal substrate.



Test with 120 lbs of air pressure at the tool for composite.

PPG1500™ Flat Head

Part Number	Length	Diameter	Head	Color	# / Case	Cases/ Skid	
HSNS112113PHG	1½"	.113	#2 PH	Gray	1,600	80	
HSNS112113T15C	1½"	.113	T-15	Cedar	1,600	80	

For use with Wood to Steel applications.

Interior Use or Weatherproof Applications

Yellow Zinc Coated – Flat Head

Part Number	Length	Diameter	Head	# / Case	Cases/ Skid	
HSNS114113YZPH	1¼"	.113	#2 PH	3,600	56	
HSNS112113YZPH	1½"	.113	#2 PH	3,600	56	

Good for Metal Applications (12-16 gauges). Yellow zinc is for interior or weatherproof applications.

See pages 78-79 for compatible nailers.