

## 20/22° BNS Plastic Strip

### Yellow Zinc Coated – Flat Head

Part Number	Length	Diameter	Head	#/Case	Cases/Skid
HDNS134120YZSQ	1¾"	.120	#2 SQ	2,000	100
HDNS200113YZPH	2"	.113	#2 PH	2,000	100
HDNS200131YZSQ	2"	.131	#2 SQ	2,000	100
HDNS214113YZPH	2¼" ★	.113	#2 PH	1,500	100
HDNS214113YZSQ	2¼" ★	.113	#2 SQ	1,500	100
HDNS214113YZPH4	2¼" ★	.113	#2 PH	4,000	48
HDNS212120YZPH	2½"	.120	#2 PH	1,500	100
HDNS212120YZSQ	2½"	.120	#2 SQ	1,500	100
HDNS300113YZPH	3" ★	.113	#2 PH	1,000	100
HDNS314120YZPH	3¼"	.120	#2 PH	1,000	100



Flat Head NailScrews® YZ coated in Plastic Strip 20° for most Framing Nailers. We recommend 2¼" x .113 and 2½" x .120 Ballistic NailScrews® for roof decking. ★ IAPMO #0133

If using ACQ Treated Lumber, exterior coatings such as PT2000®, PPG1500™, or Stainless Steel are recommended. See the Cross Reference on pages 50-52 or the Fastener/Collation Matrix on page 49.



Big Dave using the UFO NSD9021 NailScrew® Driver.



NSDGT9021FRH Gas Tool

**TIP** If using a pneumatic tool, test with 110 lbs. of air pressure at the tool on OSB and plywood.

**Drive them in;  
Screw them out!™**

See pages 78-79 for compatible nailers.