

## 15° BNS Plastic Sheet Coil

### Yellow Zinc Coated – Flat Head

| Part Number    | Length | Diameter | Head  | # / Case | Cases/ Skid |  |
|----------------|--------|----------|-------|----------|-------------|--|
| HSNS114113YZPH | 1¼"    | .113     | #2 PH | 3,600    | 56          |  |
| HSNS112113YZPH | 1½"    | .113     | #2 PH | 3,600    | 56          |  |

For use with wood underlayment or fiber-cement board to wood. Use yellow zinc coated Ballistic NailScrews® for interior applications where moisture is not present.

### PPG1500™ Flat Head

| Part Number    | Length | Diameter | Head  | Color | # / Case | Cases/ Skid |  |
|----------------|--------|----------|-------|-------|----------|-------------|--|
| HSNS112113PHG  | 1½"    | .113     | #2 PH | Gray  | 1,600    | 80          |  |
| HSNS112113T15C | 1½"    | .113     | T-15  | Cedar | 1,600    | 80          |  |

Use PPG1500™ coated Ballistic NailScrews® where moisture may be present such as kitchens and bathrooms that require extra corrosion protection or treated lumber is used. **Make sure Ballistic NailScrews® are flush. Do not over drive for this application.**



Test on scrap materials at 100-110 lbs of pressure at the tool. A depth of drive adjustment to the tool will make this easy!



## Quit Screwin' Around; Go Ballistic!™

See pages 78-79 for compatible nailers.