






15° BNS Wire Coil

NSDCN75

Yellow Zinc Coated – Flat Head






Part Number	Length	Diameter	Head	# / Case	Cases/ Skid
WCNS134113YZPH	1¾"	.113	#2 PH	3,600	56
WCNS200113YZPH	2"	.113	#2 PH	3,600	56
WCNS200113YZSQ	2"	.113	#2 SQ	3,600	56
WCNS214113YZPH	2¼" ★	.113	#2 PH	3,600	56
WCNS214113YZSQ	2¼" ★	.113	#2 SQ	3,600	56
WCNS212113YZPH	2½" ★	.113	#2 PH	3,600	56
WCNS212113YZSQ	2½" ★	.113	#2 SQ	3,600	56
WCNS300120YZSQ	3"	.120	#2 SQ	3,600	56

Yellow Zinc is for interior use or dry areas. ★ IAPMO #0133

PT2000® Flat Head – Dark Gray

Part Number	Length	Diameter	Head	#/Case	Cases/Skid
PTWCNS134113SQ	1¾"	.113	#2 SQ	800	96
PTWCNS200113SQ	2"	.113	#2 SQ	800	96
PTWCNS212113SQ	2½" ★	.113	#2 SQ	800	96
PTWCNS300113SQ	3" ★	.113	#2 SQ	800	96

PPG1500™ is for exterior use, treated lumber, and damp or wet areas. ★ IAPMO #0133

Ballistic NailScrews® can be used with Plasti-Grip® CBW (1¾" dia.), CBW2 (2" dia.) or PBLP2 (2" dia.) washers for attaching foam board insulation. Nose adaptors are available for specific UFO tools which hold the washer in place for rapid & depth controlled installation.



2" dia. Plasti-Grip® PBLP2 on EPS Foam



Plasti-Grip® CBW & CBW2 on Thermax® ci