

## 20°-22° Plastic Strip Collation for Framing Nailers including: Hitachi, Duo-Fast, Porter Cable, Senco, and others.

### Flat Head BNS for OSB, Plywood, SYP, Oak, Fur, Spruce, and other NON-Treated Lumber applications / Interior Use

Item Number	Shear Value in lbs. (Est. Avg)	Withdrawal in lbs. (Est. Avg)	Inches Length	MM Length	Inches Dia.	MM Dia.	Head Insert	Coating
HDNS134120YZSQ	1321	323	1-3/4"	44.4	0.120	3.05	#2 SQ	YZ
HDNS200113YZPH	1284	427	2"	50.8	0.113	2.87	#2 PH	YZ
HDNS200131YZSQ	1779	541	2"	50.8	0.131	3.33	#2 SQ	YZ
HDNS214113YZPH	1239	533	2-1/4"	57.1	0.113	2.87	#2 PH	YZ
HDNS214113YZSQ	1239	533	2-1/4"	57.1	0.113	2.87	#2 SQ	YZ
HDNS214113YZPH4	1239	533	2-1/4"	57.1	0.113	2.87	#2 PH	YZ
HDNS212120YZPH	1516	709	2-1/2"	63.5	0.120	3.05	#2 PH	YZ
HDNS212120YZSQ	1516	709	2-1/2"	63.5	0.120	3.05	#2 SQ	YZ
HDNS300113YZPH	1289	573	3"	76.2	0.113	2.87	#2 PH	YZ
HDNS314120YZPH	1500	800	3-1/4"	82.55	0.120	3.05	#2 PH	YZ

### Combo Head BNS for Soft Composites and ACQ, CCA, MCQ, and all other Pressure Treated Lumber / Exterior Use

PTHDNS214CSQB	1500	650	2-1/4"	57.1	0.120	3.05	#2 SQ	Brown PPG
PTHDNS214CSQT	1500	650	2-1/4"	57.1	0.120	3.05	#2 SQ	Tan PPG
PTHDNS214CSQC	1500	650	2-1/4"	57.1	0.120	3.05	#2 SQ	Cedar PPG
PTHDNS214CSQG	1500	650	2-1/4"	57.1	0.120	3.05	#2 SQ	Gray PPG
PTHDNS212CSQ	1500	700	2-1/2"	57.1	0.120	3.05	#2 SQ	Gray PPG

### Flat Head BNS for ACQ, CCA, MCQ, and all other Pressure Treated Lumber / Exterior Use

PTHDNS134113PH	1280	325	1 3/4"	44.4	0.113	2.87	#2 PH	Gray PPG
PTHDNS200113PH	1280	427	2"	50.8	0.113	2.87	#2 PH	Gray PPG
PTHDNS212113PH	1280	550	2-1/2"	63.5	0.113	2.87	#2 PH	Gray PPG
PTHDNS212113SQ	1280	550	2-1/2"	63.5	0.113	2.87	#2 SQ	Gray PPG
PTHDNS300113PH	1289	573	3"	76.2	0.113	2.87	#2 PH	Gray PPG
PTHDNS300113SQ	1289	573	3"	76.2	0.113	2.87	#2 SQ	Gray PPG

### Trim Head BNS for Harder Composites or Wood materials including all Pressure Treated Lumber / Exterior Use

PTHDNS214113TH	1239	533	2-1/4"	57.1	0.113	2.87	T-15	Gray PPG
PTHDNS214113THB	1239	533	2-1/4"	57.1	0.113	2.87	T-15	Brown PPG
PTHDNS214113THC	1239	533	2-1/4"	57.1	0.113	2.87	T-15	Cedar PPG
PTHDNS214113THG	1239	533	2-1/4"	57.1	0.113	2.87	T-15	Gray PPG
PTHDNS214113THT	1239	533	2-1/4"	57.1	0.113	2.87	T-15	Tan PPG
PTHDNS300113TH	1239	533	3"	76.2	0.113	2.87	T-15	Gray PPG

We design BNS for real world applications and use only the best coatings and materials for our Pneumatically Driven Screws!

Third party testing has been done on UFO Ballistic NailScrews® and coating materials like PPG (Pittsburgh Paint Group) and PT2000® since 2003.

Intertek Test Report No. 3100366-001 Issued July 2006 for Est. Avg. Shear and Withdrawal in SYP on all BNS manufactured at that time.

IAPMO ES Report # 0133, Issued 2009-2012 for Subfloor and Shear Walls. Annual QC checks required by IAPMO!

Lifetime Limited Warranty