

15° Wire Coil Collation for Framing Nailers including: Hitachi, MAX, Bostitch, Senco, and others.

Flat Head BNS for OSB, Plywood, SYP, Oak, Fur, Spruce, and other NON-Treated Lumber applications / Interior Use

Item Number	Shear Value in lbs. (Est. Avg)	Withdrawal in lbs. (Est. Avg)	Inches Length	MM Length	Inches Dia.	MM Dia.	Head Insert	Coating
WCNS134113YZPH	1239	350	1-3/4"	44.45	0.113	2.87	#2 PH	YZ
WCNS200113YZSQ	1250	427	2"	50.80	0.113	2.87	#2 SQ	YZ
WCNS200113YZPH	1250	427	2"	50.80	0.113	2.87	#2 PH	YZ
WCNS214113YZSQ	1218	525	2-1/4"	57.15	0.113	2.87	#2 SQ	YZ
WCNS214113YZPH	1218	525	2-1/4"	57.15	0.113	2.87	#2 PH	YZ
WCNS212113YZPH	1329	534	2-1/2"	63.50	0.113	2.87	#2 PH	YZ
WCNS212113YZSQ	1329	534	2-1/2"	63.50	0.113	2.87	#2 SQ	YZ
WCNS300120YZSQ	1516	600	3"	76.20	0.120	3.05	#2 SQ	YZ
WCNS300131YZSQ	1800	800	3"	76.20	0.131	3.33	#2 SQ	YZ
WCNS312131YZSQ	1800	900	3-1/2"	88.90	0.131	3.33	#2 SQ	YZ
WCNS200113YZSQH	1250	427	2"	50.80	0.113	2.87	#2 SQ	YZ
WCNS214113YZSQH	1218	525	2-1/4"	57.15	0.113	2.87	#2 SQ	YZ
WCNS212113YZSQH	1329	534	2-1/2"	63.50	0.113	2.87	#2 SQ	YZ

Combo Head BNS for Soft Composites and ACQ, CCA, MCQ, and all other Pressure Treated Lumber / Exterior Use

PTWCNS214CSQ	1516	525	2-1/4"	57.1	0.120	3.05	#2 SQ	PT2000®
--------------	------	-----	--------	------	-------	------	-------	---------

Flat Head BNS for ACQ, CCA, MCQ, and all other Pressure Treated Lumber / Exterior Use

PTWCNS134113SQ	1239	350	1-3/4"	44.4	0.113	2.87	#2 SQ	PT2000®
PTWCNS200113SQ	1250	427	2"	50.8	0.113	2.87	#2 SQ	PT2000®
PTWCNS212113SQ	1329	534	2-1/2"	63.5	0.113	2.87	#2 SQ	PT2000®
PTWCNS300113SQ	1289	573	3"	76.2	0.113	2.87	#2 SQ	PT2000®

Trim Head BNS for Harder Composites or Wood materials including all Pressure Treated Lumber / Exterior Use

PTWCNS214113TH	1218	525	2-1/4"	57.1	0.113	2.87	T-15	PT2000®
----------------	------	-----	--------	------	-------	------	------	---------

White Head - Trim Head BNS for White Trim (Composite or Wood) and all Pressure Treated Lumber / Exterior Use

PTWCNS214113THW	1218	525	2-1/4"	57.1	0.113	2.87	T-15	PT2000®
-----------------	------	-----	--------	------	-------	------	------	---------

316 Stainless Steel Trim Head BNS for Softer Composite and all Pressure Treated Lumber / Exterior Use

SSWCNS300120TH	NA	NA	3"	76.2	0.120	3.05	T-15	316 ST. ST.
----------------	----	----	----	------	-------	------	------	-------------

We design BNS for real world applications and use only the best coatings and materials for our Pneumatically Driven Screws!

Third party testing has been done on UFO Ballistic NailScrews® and coating materials like PPG (Pittsburgh Paint Group) and PT2000® since 2003.

Intertek Test Report No. 3100366-001 Issued July 2006 for Est. Avg. Shear and Withdrawal in SYP on all BNS manufactured at that time.

IAPMO ES Report # 0133, Issued 2009-2012 for Subfloor and Shear Walls. Annual QC checks required by IAPMO!

Lifetime Limited Warranty