

**15° Plastic Sheet Coil Collation for Siding Nails including: Hitachi, MAX, Bostitch, Senco, and others.**

**Flat Head YZ BNS for Crate Tops of OSB, Plywood, SYP, Oak, Fur, Spruce, and other NON-Treated Lumber applications / Interior Use**

**Note: BNS of .113 Diameter are great for attaching many materials to Metal (12-16 gauge) joist or studs, etc.**

Item Number	Shear Value in lbs. (Est. Avg)	Withdrawal in lbs. (Est. Avg)	Inches Length	MM Length	Inches Dia.	MM Dia.	Head Insert	Coating
HSNS114113YZPH	1097	500 in 16ga 350	1-1/4"	31.75	0.113	2.870	#2 PH	YZ
HSNS112113YZPH	1097	500 in 16ga 350	1-1/2"	38.1	0.113	2.870	#2 PH	YZ

**Combo Head BNS for most Composite and Wood Fencing and Decking to Metal joist (12-16 gauge) / Exterior Use**

HSNS112113THC	1097	500 in 16ga 350	1-1/2"	38.1	0.113	2.870	T-15	Cedar PPG
HSNS112113THT	1097	500 in 16ga 350	1-1/2"	38.1	0.113	2.870	T-15	Tan PPG

**Flat Head BNS for Concrete Boards, Composite and Wood Fencing and Decking to Metal joist (12-16 gauge) / Exterior Use**

HSNS112113PHG	1097	500 in 16ga 350	1-1/2"	38.1	0.113	2.870	#2 PH	Gray PPG
HSNS112113T15C	1097	500 in 16ga 350	1-1/2"	38.1	0.113	2.870	T-15	Cedar PPG

**Flat Head BNS for GeoDeck Composite Decking, PVC decking, all Wood Decking, Fencing, etc. / Exterior Use**

HSNS212113PSQC	1329	534	2-1/2"	63.5	0.113	2.870	#1 SQ	Cedar PPG
HSNS212113PSQG	1329	534	2-1/2"	63.5	0.113	2.870	#1 SQ	Gray PPG
HSNS212113PSQM	1329	534	2-1/2"	63.5	0.113	2.870	#1 SQ	Mahogany
HSNS212113PSQW	1329	534	2-1/2"	63.5	0.113	2.870	#1 SQ	Walnut

**We design BNS for real world applications and use only the best coatings and materials for our Pneumatically Driven Screws!**

Third party testing has been done on UFO Ballistic NailScrews® and coating materials like PPG (Pittsburgh Paint Group) and PT2000® since 2003.

Intertek Test Report No. 3100366-001 Issued July 2006 for Est. Avg. Shear and Withdrawal in SYP on all BNS manufactured at that time.

IAPMO ES Report # 0133, Issued 2009-2012 for Subfloor and Shear Walls. Annual QC checks required by IAPMO!

Lifetime Limited Warranty

## Coarse Thread Construction Screws Cross-Reference

UFO's Ballistic NailScrews®	Replaces Screw Number
.113 nominal wire size with a major thread diameter of .125	6, 7, or 8
.120 nominal wire size with a major thread diameter of .135	8 or 9
.131 nominal wire size with a major thread diameter of .146	9 or 10
.148 nominal wire size with a major thread diameter of .165	10 or 12