

## Point Locator™ Series 34° Paper Tape Collation for NSDPP38/40

Flat Head BNS for OSB, Plywood, SYP, Oak, Fur, Spruce, and other NON-Treated Lumber applications / Interior Use

Full Thread Point Locator™ BNS for exact applications: Mantis Hidden Deck Clips to IronDeck Metal Joist (12-16 gauge).

Item Number	Shear Value in lbs. (Est. Avg)	Withdrawal in lbs. (Est. Avg)	Inches Length	MM Length	Inches Dia.	MM Dia.	Head Insert	Coating
PLNS112113SQST	1097	500 in 16ga	1-1/2"	38.1	0.113	2.870	#1 SQ	Black PPG

*Point Locator™ BNS for exact applications: Mantis and all Hidden Deck Clips, Hinges, Metal Brackets, etc.*

PTPPNS112113SQB	1097	500 in 16ga	1-1/2"	38.1	0.113	2.870	#1 SQ	Black PPG
SSPPNS112113SQB	1097	500 in 16ga	1-1/2"	38.1	0.113	2.870	#1 SQ	SS w/ Black PPG

We design BNS for real world applications and use only the best coatings and materials for our Pneumatically Driven Screws!

Third party testing has been done on UFO Ballistic NailScrews® and coating materials like PPG (Pittsburgh Paint Group) and PT2000® since 2003.

Intertek Test Report No. 3100366-001 Issued July 2006 for Est. Avg. Shear and Withdrawal in SYP on all BNS manufactured at that time.

IAPMO ES Report # 0133, Issued 2009-2012 for Subfloor and Shear Walls. Annual QC checks required by IAPMO!

Lifetime Limited Warranty

## THE ELIMINATOR™

