

Before using your NailScrew[®] Driver, please read and follow all safety rules and operating instructions.

1. **KEEP CHILDREN AWAY.** All children should be kept away from the work area. Do not allow them to handle the tool.
2. **USE SAFETY GLASSES AND EAR PROTECTION.** Air tool operators and others in the work area should always wear safety glasses to prevent injury from fasteners and flying debris during use and when loading and unloading a tool. Wear ear protection to safeguard against hearing loss. (See Fig. 1.)
3. **NEVER USE OXYGEN, COMBUSTIBLE FUELS, OR ANY OTHER BOTTLED GAS** as a power source as it will cause explosion and serious personal injury. (See Fig. 2.)
4. **DO NOT CONNECT TOOL TO COMPRESSED AIR WITH PRESSURE EXCEEDING 120 PSI.**
5. **DO NOT USE AN EXCESSIVELY LONG AIR HOSE** in the working area as it will create an operator tripping hazard. Secure all connections tightly.
6. **CARRY TOOL ONLY BY THE HANDLE** and keep your finger off the trigger pull. This will allow the safety yoke mechanism to prevent the unintentional firing of fasteners.
7. **KEEP THE TOOL POINTED AWAY FROM YOURSELF AND OTHERS** at all times. Keep hands and all body parts away from the nose area and rear area of the tool to guard against possible injury.
8. **DISCONNECT TOOL FROM AIR SUPPLY BEFORE LOADING FASTENERS** to prevent accidental fastener firing. (See Fig. 3.)
9. **DO NOT DEPRESS TRIGGER OR SAFETY MECHANISM DURING FASTENER LOADING** to prevent the unintentional firing of a fastener that can cause personal injury.
10. **DISCONNECT TOOL FROM AIR SUPPLY HOSE** and disconnect from air compressor before performing maintenance, altering accessories, or while not in operation.
11. **DO NOT OPERATE ON SCAFFOLDINGS OR LADDERS**, and do not work in airtight containers or vehicles.
12. **DO NOT DRIVE FASTENERS CLOSE TO THE EDGE OF THE WORK PIECE.** The work piece could split, causing the fastener to fly free or ricochet, causing personal injury.
13. **DO NOT DRIVE FASTENERS ON TOP OF OTHER FASTENERS** or the fasteners can ricochet causing personal injury.
14. **NEVER USE A TOOL THAT IS LEAKING AIR, HAS MISSING OR DAMAGED PARTS, OR IS IN NEED OF REPAIR.** Make sure that all screws are securely tightened.
15. **INSPECT DAILY FOR FREE MOVEMENT** of trigger, safety mechanism and spring to insure safe and proper operation of the tool.
16. **ONLY USE PARTS AND ACCESSORIES RECOMMENDED BY THE MANUFACTURER.**
Tool Parts & Service Contact: <http://elder-hayesinc.com> or call 1-800-769-0775.

Fig. 1





Fig. 2



Fig. 3



See pages 78-79 for compatible nailers.