

PRESERVED WOOD FOR TODAY'S ENVIRONMENT



FASTENER INFORMATION SHEET

Fasteners for use with Preserve® and Preserve Plus® treated wood include:

- Hot-Dip galvanized
- Stainless Steel
- Other fasteners and hardware as recommended by the hardware manufacturer.

As a minimum requirement for use with treated wood, hot dip galvanized coated fasteners should conform to ASTM Standard A153 and hot dip zinc plated connectors should conform to ASTM Standard A653 (Class G-185). For optimum performance and longevity in treated wood, fasteners and connectors fabricated from stainless steel should be considered. Other types of screws and connectors coated with proprietary anti-corrosion technologies are also available for use with treated wood. Consult individual fastener manufacturer's recommendations for information about the performance of their products with treated wood.

Electroplated galvanized fasteners are not normally recognized as being corrosion resistant for exterior applications. **Aluminum should not be used in direct contact with CCA or ACQ treated lumber.**

List of hardware manufacturers that recommend hardware for use with Alkaline Copper Quaternary (ACQ) treated wood. **

Manufacturer	Product Type
Darquest Industries	Dura-Guard Nails and Screws Proprietary
FASTAP Inc.	FASTAP Poly ² ™ Wood/Poly Composite Screws
GRK Fasteners	GRK Climatek Coated Screw
Maze Nails	Double Hot-Dipped Zinc Coated Stormguard® Nails, Stainless Steel
Mid-America	Weatherwise Combo Screws
Olympic Manufacturing Group, Inc.	Fasten Master Guard Dog Pressure Treated Deck Screw
Osiose	ProDrive Outdoor Screws
Paslode	Duofast Nails Stainless Steel
Phillips Fastener Products Inc.	DeckMate with Evercoat® Screws Phillips II Outdoor/Exterior with Durafast Screws
Plating Technology, Inc.	PT2000 Nails and Screws
Prime Source Building Products	PrimeGuard Plus – Coated Fasteners
Prudential	S/S Screws
Quik Drive Screws	Stainless Steel • WSNTLG (N2000) • DTHG (Quikguard)
Renown Specialties Co., Ltd.	TIMERTIE® Triple-Zinc G185 Lumber Connectors
Simpson Strong-Tie® Co., Inc.	ZMAX (G185) Hot-Dip Galvanized or Stainless Steel Connectors
Stalgard Deck Screw	Red, Wood Grain Tan, Silver
Swan Secure Nails	Silicon Bronze; Stainless Steel
USP Structural Connectors™	Triple Zinc G-185 Connectors
York Manufacturing, Inc.	York Shield 106 Flashing & Termite Shield

* This information is correct at the time of printing.

** This information sheet contains general information only. Please refer to hardware manufacturer's product literature or website for manufacturer's recommendations and further information.



2003 International Residential Code – Fastener Statement – Section R319.3

"Fasteners for pressure-preservative treated wood shall be of hot-dipped galvanized steel, stainless steel, silicon bronze or copper. Exception: one-half inch (12.7mm) diameter or greater steel bolts."

Signature

Pratish Technology Inc
Company

10/13/03
Date